

ColorFast Finish is a high performance finish that enhances the appearance and extends the longevity of polished, integrally colored, dyed, and stained concrete, adding shine, stain resistance and abrasion resistance. Effective on concrete and cementitious surfaces that are “stained” or “coated”, this water-based, lithium-fortified product dries quickly to a clear, extremely hard micro-coating that bonds with and protects the substrate. Because of its unique chemistry, **ColorFast Finish** will not lift or peel from the surface, and periodic recoating requires no stripping. This product extends the longevity of the surface and eliminates the need for waxes, polishes and acrylics. **ColorFast Finish** is non-toxic, non-hazardous, and VOC compliant in all areas of the world.

1st coat: 1,500-3000 ft² per gal (36.8-73.6 m² per liter)

**Coverage rate will vary with concrete porosity and environmental conditions.*

Apply only when temperatures will be above 40°F (4°C) for at least 2 hours following application.

Surface Preparation: Deep clean the surface with an auto scrubber to remove any dirt, laitance, curing compounds or coatings that may prevent **ColorFast Finish** from penetrating the surface. Wipe with microfiber pad, and perform a white-rag wiping test to ensure all dirt and dust has been removed. Do not use citrus or acidic cleaners. If acidic or d-limonene cleaners have been used, neutralize the surface using an alkaline cleaner (TSP, Tide laundry detergent, etc.).

Application: Do not over mix; avoid bubbles or foaming that can make uniform application more difficult. Do not overapply. Very thin coats are best. Apply **ColorFast Finish** using a combination of a low pressure sprayer and a microfiber pad that has been pre-dampened with the product. Spray on lightly and then spread material thinly and evenly using the microfiber pad. Backpack applicator systems are recommended because they increase application efficiencies and reduce

labor. For best results, use joint lines as starting and stopping points. Do not over-work material into the surface - spread it and leave it. Allow each application to dry at least 30-60 minutes between coats or before using. Second applications will improve sheen and stain protection. Buffing with a highspeed burnisher (1500-2100 rpm) and a hog's hair pad between coats is recommended and will speed curing and improve shine. Do not cover treated surfaces for at least 1 week as protective coverings may slow curing and cause some whitening by trapping moisture. The surface is ready for use when dry.

**Before application, always do a small test sample in a less-visible area to be sure there are no variables or contaminants in the substrate that may be incompatible with this product.*

Use soap and water to clean tools and equipment. Although **ColorFast Finish** is non-toxic and environmentally safe, it is alkaline. Use up or dry out extra material and dispose of according to local regulations. Do not pour into sewer systems or storm drains.

Routine sweeping, mopping, washing and mechanical scrubbing of floors with water and **Pentra-Clean (CR)** or neutral pH cleaners is recommended. Plain water is sufficient for most environments. DO NOT USE cleaners that are acidic or that have citrus (d- Limonene) or Butyl compounds. Consult a Convergent Concrete representative for further information.

KEEP OUT OF REACH OF CHILDREN.

Do not drink. Wear goggles and gloves. Surfaces may be slippery when wet with product.

-EYES: Flush with water for 15 minutes. Seek medical attention.

-SKIN: Wash with soap and water. If irritated, seek medical attention.

-**INHALATION:** Remove to fresh air. Resuscitate if necessary. Get medical attention.

-INGESTION: Drink two large glasses of water. Get immediate medical attention.

Additional precautions, safety information and first aid treatments are contained in the Safety Data Sheet (SDS).

BY *Convergent*

High-gloss Stain and Wear Protector

- Enhances appearance of colored floors and prolongs/protects color quality
- Out-performs floor waxes, polishes and acrylics
- Delivers rapid gloss with increased abrasion and stain resistance
- Keeps dirt and contaminants from penetrating
- User friendly, dries in minutes with low odor

- This product will not alter the profile of a surface
- Forms a protective microfilm that is breathable, hard, and will not peel or flake
- Reduces maintenance and cleaning costs
- Re-application is simple and requires no stripping
- Safe for food contact per SGS Testing (21 CFR 175.300)
- VOC compliant, may contribute to LEED points (IEQ credit)

Patented Technologies by Advan

5-Gal Pail • 18.93 L

Convergent Concrete Technologies, LLC
115 North 1380 West • Orem, Utah 84057
TOLL-FREE: 866-375-2280 • OFFICE: 801-375-2280



This product is alkaline. Avoid contact with eyes and skin. Keep out of reach of children. The product may be harmful if it is inhaled or swallowed.

WARRANTY : LIMITED WARRANTY NOTICE. Every reasonable effort is made to apply exacting standards both in the manufacture of our products and in the information that we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, **CONVERGENT CONCRETE TECHNOLOGIES, L.P. ("CONVERGENT") MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING ANY PRODUCTS, SERVICES OR PARTS, AND CONVERGENT SHALL HAVE NO OTHER LIABILITY WITH RESPECT THERETO.** Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of CONVERGENT'S Research Director. This information and all further technical advice are based on CONVERGENT'S present knowledge and experience. However, CONVERGENT disclaims any liability for reliance upon such information or advice, including such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, CONVERGENT disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. CONVERGENT SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. CONVERGENT reserves the right to make any changes according to technological progress or further developments. It is the customer's (Authorized Applicator) responsibility and obligation to carefully inspect and test any incoming goods. Performance of the products described herein is verified by testing that is carried out by or on behalf of qualified experts. It is the sole responsibility of the customer to carry out the arrangements for such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used. CONVERGENT reserves the right to change specifications referred to in this literature at any time, without prior notice. The information contained herein is, to our knowledge, true and accurate. While this material is furnished in good faith, no warranty expressed or implied, of merchantability, completeness, fitness or otherwise is made. This material is offered only for your consideration, investigation and verification, and CONVERGENT disclaims any liability incurred from the use thereof and shall not in any event, be liable for any special, incidental or consequential damages resulting from the use of this information. The user shall be responsible for the manner and conditions of use and handling of any material may involve other or additional considerations specific to the use or user. Nothing herein should be construed as permission or recommendation to infringe any patent or as to any specific use. No agent, representative or employee of this company is authorized to vary any term of this notice.



**FOR MORE INFORMATION
AND PRODUCT
SPECIFICATIONS**
Visit our website
www.convergentconcrete.com
or scan the QR code.

©2021 Convergent Concrete Technologies, LLC. All Rights Reserved. COLORFAST FINISH is a registered trademark of Convergent Concrete Technologies, LLC. Nano-Lithium® brand name and logo are registered trademarks of Advanced Concrete Technologies, LLC ("ADVAN") and sub-licensed to Convergent Concrete Technologies, LLC, under a non exclusive co-brand/technology license. All rights reserved. ADVANCED CONCRETE TECHNOLOGIES, LLC makes no claim as to the product performance or product shown to be other than as warranted. REVISION DATE 01/28/21